

nBOLLARD SLIM

Lumen output [lm]	324 - 608lm
Luminous flux tolerance	10%
Angle of distribution	360
IP protection class	IP65
Impact resistance	IK10
Working temperature range	-30˚C ÷ +45˚C
Lifetime L80B10	50 000H
Protection class	I
Wiring	3x1mm²
Connection	0.5m
Dimming	ON-OFF / DALI / SENSOR
Power supply type	220-240V AC

nBOLLARD SLIM

ORDER CODE AND TECHNICAL SPECIFICATIONS OF VARIANTS

VARIANT CODES IN THE TABLE BELOW TECHNICAL SPECIFICATIONS OF VARIANTS IN DATASHEET OF VARIANT

ENVIRONMENTAL CAUTION!

It is prohibited to dispose of obsolete and waste electrical and electronic equipment together with regular household wastes. They should be properly sorted and recycled. Old electrical and electronic equipment should be returned to a waste collection point established by a waste-management service. Waste electrical and electronic equipment can be broken down to base materials and then recycled. For more information regarding waste management please contact your local authorities, waste-management service or the seller of electrical and electronic devices.

ORDER CODE AND TECHNICAL SPECIFICATIONS OF VARIANTS

Lumen output [lm]	Index	Power supply type	EAN
324lm	NBOLLARD-SLIM-6-VW-360-350-AM-HV-O	220-240V AC	5905658721015
324lm	NBOLLARD-SLIM-6-NW-360-350-AM-HV-D	220-240V AC	5905658721107
608lm	NBOLLARD-SLIM-12-NW-360-750-BM-HV-O	220-240V AC	5905658721237
324lm	NBOLLARD-SLIM-6-VW-360-350-AM-HV-D	220-240V AC	5905658721022
324lm	NBOLLARD-SLIM-6-WW-360-350-BM-HV-O	220-240V AC	5905658721077
608lm	NBOLLARD-SLIM-12-VW-360-750-BM-HV-D	220-240V AC	5905658721169
608lm	NBOLLARD-SLIM-12-WW-360-750-BM-HV-O	220-240V AC	5905658721190
608lm	NBOLLARD-SLIM-12-VW-360-750-AM-HV-D	220-240V AC	5905658721145
324lm	NBOLLARD-SLIM-6-VW-360-350-BM-HV-O	220-240V AC	5905658721039
608lm	NBOLLARD-SLIM-12-WW-360-750-AM-HV-O	220-240V AC	5905658721176
324lm	NBOLLARD-SLIM-6-VW-360-350-BM-HV-D	220-240V AC	5905658721046
324lm	NBOLLARD-SLIM-6-NW-360-350-BM-HV-O	220-240V AC	5905658721114
608lm	NBOLLARD-SLIM-12-NW-360-750-AM-HV-D	220-240V AC	5905658721220
324lm	NBOLLARD-SLIM-6-WW-360-350-AM-HV-O	220-240V AC	5905658721053
608lm	NBOLLARD-SLIM-12-VW-360-750-AM-HV-O	220-240V AC	5905658721138
608lm	NBOLLARD-SLIM-12-VW-360-750-BM-HV-O	220-240V AC	5905658721152
608lm	NBOLLARD-SLIM-12-NW-360-750-BM-HV-D	220-240V AC	5905658721244
324lm	NBOLLARD-SLIM-6-WW-360-350-AM-HV-D	220-240V AC	5905658721060
608lm	NBOLLARD-SLIM-12-WW-360-750-AM-HV-D	220-240V AC	5905658721183
324lm	NBOLLARD-SLIM-6-NW-360-350-BM-HV-D	220-240V AC	5905658721121
324lm	NBOLLARD-SLIM-6-WW-360-350-BM-HV-D	220-240V AC	5905658721084
608lm	NBOLLARD-SLIM-12-NW-360-750-AM-HV-O	220-240V AC	5905658721213
324lm	NBOLLARD-SLIM-6-NW-360-350-AM-HV-O	220-240V AC	5905658721091
608lm	NBOLLARD-SLIM-12-WW-360-750-BM-HV-D	220-240V AC	5905658721206

Niviss reserves the right to make technical changes without prior notice
product_card_20261115_222152