TUBE XL



Lumen output [lm]	2500 - 2790 lm
Luminous flux tolerance	10%
Angle of distribution	10, 15, 24, 36, 60
IP protection class	IP65
Impact resistance	IK06
Working temperature range	-35°C ÷ +65°C
Lifetime L80B10	≥ 75 000 h
Protection class	HV: I / LV: III
Wiring	H05RN
Connection	0,15 m
Dimming	ON-OFF / DALI / DALI 2 (based on external drivers)
Power supply type	HV: 100-245V AC 50/60Hz / LV: 24V DC

Niviss reserves the right to make technical changes without prior notice
product_card_20261116_093316

TUBE XL

ORDER CODE

ENVIRONMENTAL CAUTION!

It is prohibited to dispose of obsolete and waste electrical and electronic equipment together with regular household wastes. They should be properly sorted and recycled. Old electrical and electronic equipment should be returned to a waste collection point established by a waste-management service. Waste electrical and electronic equipment can be broken down to base materials and then recycled. For more information regarding waste management please contact your local authorities, waste-management service or the seller of electrical and electronic devices.

CONTACT: +48 58 781 33 99 sales@niviss.com www.niviss.com

Niviss reserves the right to make technical changes without prior notice
product_card_20261116_093316