NIVISS

TUBE M



Lumen output [lm]	900 - 1010 lm
Luminous flux tolerance	10%
Angle of distribution	10, 15, 24, 36, 60
IP protection class	IP65
Impact resistance	IK06
Working temperature range	-35°C ÷ +65°C
Lifetime L80B10	≥ 75 000 h
Protection class	HV: I / LV: III
Wiring	H05RN
Connection	0,15 m
Dimming	ON-OFF / DALI / DALI 2 (based on external drivers)
Power supply type	HV: 100-245V AC 50/60Hz / LV: 24V DC

CONTACT: +48 58 781 33 99 sales@niviss.com www.niviss.com

Niviss reserves the right to make technical changes without prior notice
product_card_20261113_114617

TUBE M

KOD PRODUKTU

UWAGA DOTYCZĄCA ŚRODOWISKA!

Zabrania się wyrzucania przestarzałego i zużytego sprzętu elektrycznego i elektronicznego razem ze zwykłymi odpadami domowymi. Należy je odpowiednio posegregować i poddać recyklingowi. Stary sprzęt elektroniczny i elektryczny należy zwrócić do punktu zbiórki odpadów wyznaczonego przez firmę zajmującą się gospodarką odpadami. Zużyty sprzęt elektryczny i elektroniczny zostanie rozdzielony na materiały bazowe, które następnie zostaną poddane recyklingowi. Aby uzyskać więcej informacji na temat gospodarki odpadami, skontaktuj się z lokalnymi władzami, służbami zajmującymi się gospodarką odpadami lub sprzedawcą sprzętu elektronicznego i elektrycznego.